



#####

ORGANIC S1 P

#####

ORGANIC#####S1P#####SR#####

#####

####	#####
##	###
#####	SJ#####
#####	###
#####	PU/PU
#####	###
#####	S1 P / SRC
#####	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
#####	0.490 kg
##	ASTM F2413:2018 EN ISO 20345:2011



#####S1P#
#####



##



#####



#####100 KiloOhm##1 GigaOhm
#####



#####



SRC####

##SRC##SRA##SRB#####

###



DGR

#####:
#####, #####, ##, #####

#####:
####

#####:
#####

####	####	##	EN ISO 20345
####	#####		
	#####	mg/cm ² /h	6.9
	#####	mg/cm ²	61.1
##	####		
	#####	mg/cm ² /h	60.5
	#####	mg/cm ²	484.1
#####	SJ#####		
	#####	####	25600/12800
#####	PU/PU		25600/12800
	#####	mm ³	29.1
	SRA####	####	# 0.28
	SRA####	####	# 0.32
	SRB####	####	# 0.13
	SRB####	####	# 0.18
	####	####	0.1 - 1000
	ESD#	####	N/A
	#####	J	27
#####	####		
	#####100J#	mm	N/A
	#####10kN#####	mm	N/A
	#####200J#	mm	14.0
	#####15kN#	mm	14.5

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com