

###

ORGANIC S1 P

ORGANIC #####
S1P, #####
SR, #####
#####

#####	#####
#####	#####
#####	SJ #####
#####	#####
#####	PU/PU
#####	#####
#####	S1 P / #####
#####	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5
#####	JPN 21.5-26.5 / KOR 230-270
#####	0.490 kg
#####	ASTM F2413:2018
#####	EN ISO 20345:2011




S1P

#####?

S1P



#####



#####



DGR



#####

#####



#####

#####

100 ##### 1 #####



SRC

#####

SRC ##### SRA ##### SRB #####

#####:

#####, #####, #####, #####

#####:

#####

#####:####:

#####

#####		#####	#####	EN ISO 20345
#####	#####	##./##./##	6.9	# 0.8
#####	#####	##./##	61.1	# 15
#####	#####	##./##./##	60.5	# 2
#####	#####	##./##	484.1	# 20
#####	SJ #####			
#####	#####: ##### (###/###) (###)	###	25600/12800	25600/12800
#####	PU/PU			
#####	##### (#####) (#####)	##	29.1	# 150
#####	SRA: #####	#####	0.40	# 0.28
#####	SRA: ###	#####	0.39	# 0.32
#####	SRB: #####	#####	0.15	# 0.13
#####	SRB: ###	#####	0.20	# 0.18
#####	#####	#####	189.9	0.1 - 1000
#####	ESD	#####	N/A	0.1 - 100
#####	#####	##	27	# 20
#####	##### (##### 100J)	##	N/A	N/A
#####	##### (##### 10kN)	##	N/A	N/A
#####	##### (##### 200J)	##	14.0	# 14
#####	##### (##### 15kN)	##	14.5	# 14

#####:

Safety Jogger