



ORION S1 P

#####

ORION#####

####	#####
##	###
####	SJ#####
####	####
####	PU/PU
####	###
####	S1 P / SR, #####
####	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0
	JPN 22.5-31 / KOR 235-310
####	0.647 kg
##	ASTM F2413:2018
	EN ISO 20345:2022



##



#####



SRC#####
#####1#
##SRC#####SRA#SRB#####

###



##100 KiloOhm##1 GigaOhm
#####



#####S1P##
#####



#####



135

#####:
#####, ##, #####, ####

#####:
####

#####:
#####

####	####	##	EN ISO 20345
####	#####		
	#####	mg/cm ² /h	6.9
	#####	mg/cm ²	61.1
##	####		
	#####	mg/cm ² /h	86.9
	#####	mg/cm ²	695.4
#####	SJ#####		
	#####	####	25600/12800
#####	PU/PU		25600/12800
	#####	mm ³	32
	- #####NaLS - #####	#####	# 150
	- #####NaLS - #####	#####	0.47
	SR ### - ##### - #####	#####	# 0.31
	SR##### - ##### - #####	#####	0.44
	SR##### - ##### - #####	#####	# 0.36
	SR##### - ##### - #####	#####	0.26
	ESD#	#####	# 0.19
	#####	#####	0.29
		116.5	# 0.22
		N/A	0.1 - 100
		J	0.1 - 100
		30	# 20
#####	###		
	#####100J#	mm	N/A
	#####10kN#####	mm	N/A
	#####200J#	mm	17.0
	#####15kN#	mm	# 14
			21.5
			# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com