



#####

PACCO S1PS LOW

PACCOS1LOW

#####

#####PACCO S1P#####

#####ESD#####

#####

####

##

SJ#####

#####

#####/###

#####

S1 PS / SR, ESD

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.470 kg

ASTM F2413:2018


EN ISO 20345:2022



WHT



BLK




#####



#####S1P##
#####



#####100#####



#####



#####



#####ESD#
ESD#####

###100 KiloOhm##100 MegaOhm
#####

####:
##, #####, ##, #####

#####:
####, #####

#####:
#####

	####	####	##	EN ISO 20345
####	####			
	#####	mg/cm²/h	1.20	# 0.8
	#####	mg/cm²	18.50	# 15
##	####			
	#####	mg/cm²/h	34.59	# 2
	#####	mg/cm²	277	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/###			
	#####	mm³	129mm³(Density:1.16)	# 150
	##### - #####NaLS - #####	#####	0.36	# 0.31
	##### - #####NaLS - #####	#####	0.44	# 0.36
	SR ### - ##### - #####	#####	0.25	# 0.19
	SR##### - ##### - #####	#####	0.31	# 0.22
	####	#####	53.1	0.1 - 1000
	ESD#	#####	11	0.1 - 100
	#####	J	25	# 20
#####	#####			
	#####100J#	mm	NA	N/A
	#####10kN#####	mm	NA	N/A
	#####200J#	mm	15	# 14
	#####15kN#	mm	17	# 14

#####.

#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com