



## ##:  
####, ###, ##, ##

## ##:  
### ##, ## ##### ##

## ## ##:  
### ### ##### ##### ### ##### ### ##### ## #####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm <sup>2</sup> /h	1.20	# 0.8
	##: ### ##	mg/cm <sup>2</sup>	18.50	# 15
## ##	##			
	##: ### ##	mg/cm <sup>2</sup> /h	34.59	# 2
	##: ### ##	mg/cm <sup>2</sup>	277	# 20
##	<b>SJ ### # ###</b>			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	### #####(## ##)	mm <sup>3</sup>	129mm <sup>3</sup> (Density:1.16)	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.36	# 0.31
	## ### ## - ### + NaLS - ## ## ##	##	0.44	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.25	# 0.19
	SR ### ## - ### + ##### - ## ## ##	##	0.31	# 0.22
	### ## #	###	53.1	0.1 - 1000
	ESD #	###	11	0.1 - 100
	##### ## ##	J	25	# 20
<b>Top</b>	##			
	##### ## ##(## # ## 100J)	mm	NA	N/A
	##### ## ##(## # ## ## 10kN)	mm	NA	N/A
	##### ## ##(## # ## 200J)	mm	15	# 14
	##### ## ##(## # ## ## 15kN)	mm	17	# 14

### ##:

##### ## ##### ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.



www.safetyjogger.com