


SAFETY JOGGER

INDUSTRIAL



#

PACCO S1PS LOW

PACCOS1LOW

#####

#####PACCO S1P #####


##	###
##	####
##	SJ #####
##	#####
##	##/####
##	#####
##	S1 PS / SR, ESD
####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
	JPN 21.5-31.5 / KOR 230-315
####	0.470 kg
##	ASTM F2413:2018
	EN ISO 20345:2022



WHT



BLK



#####



S1P
#####/#####
#####S1P
####



100%#####
###



#####



#####



####(ESD)
ESD#####
10####35 #
#####

##:
##, ##, ##, ##

##:
####, #####

####:
#####

##	###	####	##	EN ISO 20345
##	#####	##/####/##	1.20	#### 0.8
##	#####	##/####	18.50	#### 15
##	#####	##/####/##	34.59	#### 2
##	#####	##/####	277	#### 20
##	SJ #####			
	#####/#####	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
##	#####	## ³	129mm ³ (Density:1.16)	#### 150
	##### - ## + NaLS - #####	##	0.36	#### 0.31
	##### - ## + NaLS - #####	##	0.44	#### 0.36
	SR ## - ## + ## - #####	##	0.25	#### 0.19
	SR ## - ## + ## - #####	##	0.31	#### 0.22
	####	##	53.1	0.1 - 1000
	ESD#	##	11	0.1 - 100
	####	J	25	#### 20
##	#####			
	#####100J#	##	NA	N/A
	#####10kN#	##	NA	N/A
	#####200J#	##	15	#### 14
	#####15kN#	##	17	#### 14

####:

#####Safety Jogger#####



HEAD-TO-TOE PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.



www.safetyjogger.com