



#####

PACCO S1PS LOW

PACCOS1PSL

#####

PACCO S1P#####

#####ESD#####

####

SJ#####

#####

#####/###

#####

S1 PS / SR, SC, ESD, ####, #####, #####, HRO

EU 35-48

0.530 kg

EN ISO 20345:2022+A1:2024
ASTM F2413:2024




(SR)

#####SRA+SRB=SRC#####
#####SR#####



#####

#####



#####

#####



#####ESD#

ESD#####

#####

##100 KiloOhm##100 MegaOhm

#####



#####

#####



#####

#####

##



WHT

#####:

##, #####, #####, ####, #####

#####:

####, #####, ####

#####:

#####

####		####	#	EN ISO 20345
####	####			
	#####	mg/cm²/h	4.32	# 0.8
	#####	mg/cm²	37	# 15
##	####			
	#####	mg/cm²/h	86.31	# 2
	#####	mg/cm²	691	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/###			
	#####	mm³	128	# 150
	##### - #####NaLS - #####	####	0.43	# 0.31
	##### - #####NaLS - #####	####	0.44	# 0.36
	SR ### - ##### - #####	####	0.36	# 0.19
	SR##### - ##### - #####	####	0.33	# 0.22
	####	####	37.2	0.1 - 1000
	ESD#	####	33	0.1 - 100
	#####	J	30	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	18.5	# 14
	#####15kN#	mm	23.5	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com