



###

POSEIDON S4

PVC#####

PVC#####POSEIDON#####
#####

####	SJ PVC
##	#####
#####	N/A
#####	N/A
#####	PVC
#####	####
#####	S4 / #####
#####	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
#####	1.080 kg
##	ASTM F2413:2018 EN ISO 20345:2022



###WR#



##



WHT



SRA#####
##SRA#####
#####



###100 KiloOhm##1 GigaOhm
#####



#####



#####

####:

#####, #####, ##, ####, ####

#####:

#####, #####, ####

#####:

#####

####		####	##	EN ISO 20345
####	SJ PVC			
	#####	mg/cm ² /h	N/A	# 0.8
	#####	mg/cm ²	N/A	# 15
##	####			
	#####	mg/cm ² /h	N/A	# 2
	#####	mg/cm ²	N/A	# 20
####	N/A			
	#####	####	N/A	25600/12800
#####	PVC			
	#####	mm ³	162	# 150
	##### - #####NaLS - #####	#####	0.38	# 0.31
	##### - #####NaLS - #####	#####	0.37	# 0.36
	SR ### - ##### - #####	#####	N/A	# 0.19
	SR##### - ##### - #####	#####	N/A	# 0.22
	####	#####	298.6	0.1 - 1000
	ESD#	#####	N/A	0.1 - 100
	#####	J	20	# 20
#####	####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	23.0	# 14
	#####15kN#	mm	24.0	# 14

####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com