



PROIMPACT SINGLE 4X42

PROIMPACTS

Impact Gloves

Safety Jogger PRO IMPACT gloves deliver advanced impact protection and comfort for assembly, automotive, industry and construction tasks.

Performance level	4X42CP
Liner	13 Gauge/HPPE/Polyamide/Polyester/Glass Fibre/Spandex
Coating	Foam Nitrile
Category	TSF-Touchscreen function, SIF-Silicone Free
Size range	EU 7-12
Sample weight	0.078 kg
Norms	ANSI/ISEA 105:2016 ANSI/ISEA 138-2019 EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Automotive, Assembly, Construction, Industry

Impact resistant

These gloves have extra padding to protect your palms and knuckles from impacts, reducing the risk of injury.

Excellent cut resistance

These gloves provide excellent protection against cuts, meeting the second-highest level of cut resistance according to the EN 388 standard. They are ideal for tasks with a higher risk of cuts.



514

Performance level 4X42CP

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.