



Heavy

PROMOALASK S3

Winterbox including the Alaska safety boot

Winterbox including 1 pair of Alaska safety boots, 1 pair of socks, 1 pair of winter working gloves and a warm Safety Jogger beanie

Upper	Pull-up Action Leather
Lining	Teddy
Footbed	Teddy
Midsole	Steel
Outsole	PU
Toecap	Steel
Category	S3 / CI, SRC
Size range	EU 38-47 / UK 5.0-12.0 / US 5.5-13.0 JPN 24-31 / KOR 250-310
Sample weight	0.853 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BRN



Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Warm lining

Keeps your feet warm and dry in cold environments.



Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

Industries:

Automotive, Chemical, Construction, Logistics, Mining, Oil & Gas, Industry

Environments:

Cold environment, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Pull-up Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	7.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	64	≥ 15
Lining	Teddy			
	Lining: permeability to water vapor	mg/cm ² /h	120.6	≥ 2
	Lining: water vapor coefficient	mg/cm ²	964.8	≥ 20
Footbed	Teddy			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU			
	Outsole abrasion resistance (volume loss)	mm ³	85.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	108.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.0	≥ 14

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.