

# PROSOFT 12PACK 3121X

PROSOFT12P

### **Safety Gloves With Grey Foam Nitrile Coating**

Safety Jogger PROSOFT gloves with foam nitrile coating deliver comfort, dexterity and reliable grip in dry or light oily tasks.

Performance level	3121X				
Liner	13 Gauge Polyester/Spandex/Rubber(NBR)				
Coating	Foam Nitrile				
Category	SIF-Silicone Free				
Size range	EU 6-12				
Sample weight	0.022 kg				
Norms	ANSI/ISEA 105:2016				
	EN ISO 21420:2020				
	EN 388·2016				





EN ISO 21420













## **Industries:**

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical



335

# Performance level 3121X

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	В	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

#### Touchscreen compatible

You can use your smartphone or tablet without taking off the gloves, thanks to their special coating.

### Oil resistant

The gloves can handle oils, greases, and solvents without breaking down. They are ideal for jobs involving mechanical work, or professions in the manufacturing, maintenance or the oil industry.



**HEAD-TO-TOE** PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.