

Light

## RAPTOR S1 PS

### Composite Toe Athletic Safety Shoes

RAPTOR safety shoes with active air shock absorption, S1P breathability, SR slip grip, metalfree lightweight design for multiple industries.

Upper	Mesh, Nubuck Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	Phylon/Rubber (NBR)
Toecap	Composite
Category	S1 PS / SR, FO, HRO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.615 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



077




#### S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.




#### Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity



#### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

Industries:

Automotive, Food & beverages, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Mesh, Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	4.7	# 0.8
	Upper: water vapor coefficient	mg/cm²	44.1	# 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	63.9	# 2
	Lining: water vapor coefficient	mg/cm²	511.3	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	102	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.49	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.27	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.23	# 0.22
	Antistatic value	MegaOhm	130	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	38	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.0	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com