



SAFETY JOGGER

PROFESSIONAL



Light

REMY OB

Comfort and safety clogs

The REMY clogs offer superior comfort and safety. With ESD protection, a removable footbed, and exceptional grip, they're perfect for medical and cleaning professionals.

| | |
|---------------|---|
| Upper | Action Leather |
| Lining | Mesh |
| Footbed | Oxy Basic |
| Outsole | Phylon/Rubber (NBR) |
| Category | OB / SR, ESD, A, E, HRO |
| Size range | EU 39-47 / UK 6.0-12.0 / US 6.5-13.0 JPN 25-31 / KOR 255-310 |
| Sample weight | 0.279 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2022(Europe) |



NAV



WHT



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Coolmax® lining
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:

Cleaning, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 15.2 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 28.9 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 231.3 | ≥ 20 |
| Footbed | Oxy Basic | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 89 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.44 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.37 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.36 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.28 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 21.8 | 0.1 - 1000 |
| | ESD value | MegaOhm | 26 | 0.1 - 100 |
| | Heel energy absorption | J | 31 | ≥ 20 |

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.