

SAFETY JOGGER

INDUSTRIAL

SNEAKERS

S035 S3

Sporty, low-cut safety shoe for daily protection

Upper	Nappa Action Leather
Outsole	Phylon, Rubber
Toecap	Steel
Midsole	Anti-puncture Textile
Lining	Mesh
Footbed	EVA
Safety category	EN ISO 20345 - S3 / SRC
Sample weight	0.630 gr.
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



SJ FLEX
Metal-free puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.




SRC SLIP RESISTANCE
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



STEEL TOECAP
Robust metal support to protect the feet of the wearer against falling or rolling objects.



ANTISTATIC
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



HEEL ENERGY ABSORPTION
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

SAFETY JOGGER

INDUSTRIAL

SNEAKERS

S035 S3

Industries:

Automotive, Catering, Cleaning, Construction, Food & beverages, Industry, Logistics

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	19	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	58.4	≥ 2
	Lining: water vapor coefficient	mg/cm ²	468	≥ 20
Footbed	EVA			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Phylon, Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	107	≤ 150
	Outsole slip resistance SRA: heel	friction	0.34	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.36	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	8.6	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	22	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	14.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
42