



SAFETYRUN2 S1 P

Safety shoe with steel toecap for construction/ manufacturing

The SAFETYRUN2 is a versatile, S3 safety shoe offering superior protection with a steel toecap, grip, comfort, and durability. Ideal for high-humidity environments, it prevents static charges and offers body posture support.

| | |
|---------------|---|
| Upper | Barton Action Leather |
| Lining | Mesh |
| Footbed | SJ Eco |
| Midsole | Steel |
| Toecap | Steel |
| Category | S1 P / SR, FO |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.605 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2022 |



BLK



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Mining, Oil & Gas, Industry

Environments:

Dry environment, Uneven surfaces, Muddy environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Barton Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 657.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 525.8 | ≥ 20 |
| Footbed | SJ Eco | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 16 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 17 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.