



#####

SAFETYRUN S1P PERF

SAFTYRNP

#####

#####S1##SR#####
#####

#####

####

SJ##

####

PU

####

S1 P / SR,

EU 35-47 / UK 3.0-12.0 / US 3.0-13.0

JPN 21.5-31 / KOR 230-310

0.594 kg

ASTM F2413:2018

EN ISO 20345:2022



BLK



#####100 KiloOhm##1 GigaOhm
#####



#####



#####



#####



SRC###
#####1##
##SRC#####SRA#SRB#####

####

####:
##, #####, ##, #####

#####:
####, #####

#####:
#####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm²/h	2.2	# 0.8
	#####	mg/cm²	25	# 15
##	####			
	#####	mg/cm²/h	657.7	# 2
	#####	mg/cm²	525.8	# 20
####	SJ##			
	#####	####	25600/12800	25600/12800
#####	PU			
	#####	mm³	55	# 150
	##### - #####NaLS - #####	####	0.40	# 0.31
	##### - #####NaLS - #####	####	0.39	# 0.36
	SR ## - ##### - #####	####	0.28	# 0.19
	SR##### - ##### - #####	####	0.26	# 0.22
	#####	####	270	0.1 - 1000
	ESD#	####	N/A	0.1 - 100
	#####	J	26	# 20
#####	####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	16	# 14
	#####15kN#	mm	17	# 14

#####.
#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com