



SAFETY JOGGER INDUSTRIAL

SAFETYRUN S1P PERF

SAFTYRNPER

#####

SAFETYRUN S1 #####

SR

#####

#####

SJ

PU

#####

S1 P / ####.####,

EU 35-47 / UK 3.0-12.0 / US

JPN 21.5-31 / KOR 2


0.594 kg

ASTM F2413:2018 EN ISO 20345:2022

EN ISO 20345:2022



BLK



```
##### SRC
#####
##### SRC ##### SRA #### SRB
#####
```

**SAFETY
JOGGER
WORKS**

HEAD-TO-TOE PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

#####: #####:

#####: #####

#####	#####	#####	#####	EN ISO 20345
#####	#####	##./##./##	2.2	# 0.8
#####	#####	##./##	25	# 15
#####	#####	##./##./##	657.7	# 2
#####	#####	##./##	525.8	# 20
#####	SJ #####			
#####	#####: ##### (#####/#####) (###)	##	25600/12800	25600/12800
#####	PU			
#####	##### (#####/#####)	##	55	# 150
#####	- ##### + NaLS - #####	#####	0.40	# 0.31
#####	- ##### + NaLS - #####	#####	0.39	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.28	# 0.19	
##### SR - ##### + ##### - #####	#####	0.26	# 0.22	
#####	#####	270	0.1 - 1000	
### ESD	#####	N/A	0.1 - 100	
#####	##	26	# 20	
#####	#####			
#####	(#####/##### 100J)	##	N/A	N/A
#####	(#####/##### 10kN)	##	N/A	N/A
#####	(#####/##### 200J)	##	16	# 14
#####	(#####/##### 15kN)	##	17	# 14

#####:

Safety Jogger

