



#

SAFETYRUN S1P PERF

SAFTYRNPER

#####

Safety JoggerSAFETYRUN S1 ##### SR #####
#####

##	#####
##	####
##	SJ ##
##	-
##	###PU
##	-
##	S1 P / SR, FO
####	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
####	0.594 kg
##	ASTM F2413:2018 EN ISO 20345:2022



#10###1#####



#####



#####



#####



SRC##
SRC##
#SRA#SRB#####
#####



BLK

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
##, ##, ##, ##

##:
####, #####

####:
#####

##		####	##	EN ISO 20345
##	#####			
	#####	##/####/##	2.2	#### 0.8
	#####	##/####	25	#### 15
##	####			
	#####	##/####/##	657.7	#### 2
	#####	##/####	525.8	#### 20
##	SJ ##			
	#####/#####	##	25600/12800	25600/12800
##	###PU			
	#####	## ³	55	#### 150
	#### - ## + NaLS - ####	##	0.40	#### 0.31
	#### - ## + NaLS - #####	##	0.39	#### 0.36
	SR ## - ## + ## - ####	##	0.28	#### 0.19
	SR ## - ## + ## - #####	##	0.26	#### 0.22
	####	##	270	0.1 - 1000
	ESD#	##	N/A	0.1 - 100
	####	J	26	#### 20
	-			
##	#####100J#	##	N/A	N/A
	#####10kN#	##	N/A	N/A
	#####200J#	##	16	#### 14
	#####15kN#	##	17	#### 14

####:
#####Safety Jogger#####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com