

SAFETY JOGGER


PROFESSIONAL

MOVE UP

SAMANTHA **OB**

Comfortabele veterloze schoen voor vrouwen

Upper	Nappa Leather
Outsole	EVA/Rubber
Toecap	
Midsole	
Lining	Mesh
Footbed	SJ foam footbed
Standards	EN ISO 20347 - OB / ESD, A, SRC, E
Sample weight	260 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0




OXYGRIP / SJ GRIP

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



BREATHABLE UPPER

Increased moisture and temperature management for extended wearer comfort.



SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

MOVE UP

SAMANTHA OB

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Nappa Leather			
	Upper: permeability to water vapor	mg/cm ² /h	9.4	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	78	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	43.7	≥ 2
	Lining: water vapor coefficient	mg/cm ²	350	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	81.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.47	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.21	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	70	0.1 - 100
	Heel energy absorption	J	38.9	≥ 20
Toecap				
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 13
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 13
	Impact resistance toecap (clearance after impact 200J)	mm	NA	≥ 13
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	≥ 13

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size: 38