

SANDY S3S LOW TLS

Lightweight, metal-free and low-cut safety shoe with suede leather upper and side TLS closing system

The SANDY S3S TLS is a lightweight, metal-free safety shoe for logistics, assembly, and light industry. It features a suede leather upper, memory foam footbed, and SR-rated outsole. The side TLS closure ensures a secure fit, while the composite toe cap, textile midsole, and ESD certification provide reliable protection.

| Upper | Suede Leather |
|---------------|---|
| Lining | Mesh |
| Footbed | SJ Memory foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | Phylon/Rubber (NBR) |
| Toecap | Composite |
| Category | S3S / SR, ESD, HI, CI, FO, HRO |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.564 kg |
| Norms | ASTM F2413:2018 |































Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



TLS (Twist Lock System)

Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last



Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.





Industries:

Assembly, Automotive, Industry, Logistics

Environments:

Dry environment, Wet environment, Extreme slippery surfaces, Warm surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---------|--|--------------------|---|--------------|
| Upper | Suede Leather | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 5.44 | # 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 48 | # 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 86.31 | # 2 |
| | Lining: water vapor coefficient | mg/cm ² | 691 | # 20 |
| Footbed | SJ Memory foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 128 | # 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.43 | # 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.44 | # 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.36 | # 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.33 | # 0.22 |
| | Antistatic value | MegaOhm | 37.2 | 0.1 - 1000 |
| | ESD value | MegaOhm | 19 | 0.1 - 100 |
| | Heel energy absorption | J | 30 | # 20 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 18.5 | # 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 23.0 | # 14 |

Sample size

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.





