




SAFETYBOY WINTER S1P

SFTYBOYWNT

SAFETYBOY WINTER S1#####

#####

| | |
|-------|---|
| #### | ##### |
| ## | ### |
| ##### | ### |
| ##### | ### |
| ##### | PU |
| ##### | ### |
| ##### | S1 P / SRC, ##### |
| ##### | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| ##### | 0.620 kg |
| ## | ASTM F2413:2018 EN ISO 20345:2011 |



#####



#####100 KiloOhm##1 GigaOhm
#####



#####



#####



####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

####:
##, ##, ####, #####, #####

#####:
####, #####, #####, #####

#####:
#####

| | #### | #### | ## | EN ISO 20345 |
|-------|----------------|----------|-------------|--------------|
| #### | ##### | | | |
| | ##### | mg/cm²/h | 1.18 | # 0.8 |
| | ##### | mg/cm² | 15 | # 15 |
| ## | ### | | | |
| | ##### | mg/cm²/h | 83.25 | # 2 |
| | ##### | mg/cm² | 666 | # 20 |
| #### | ### | | | |
| | ##### | #### | 25600/12800 | 25600/12800 |
| ##### | PU | | | |
| | ##### | mm³ | 78 | # 150 |
| | ##### SRA#### | #### | 0.35 | # 0.28 |
| | ##### SRA#### | #### | 0.33 | # 0.32 |
| | ##### SRB#### | #### | 0.14 | # 0.13 |
| | ##### SRB#### | #### | 0.19 | # 0.18 |
| | ##### | #### | 46.8 | 0.1 - 1000 |
| | ESD# | #### | N/A | 0.1 - 100 |
| | ##### | J | 33 | # 20 |
| ##### | ### | | | |
| | #####100J# | mm | N/A | N/A |
| | #####10kN##### | mm | N/A | N/A |
| | #####200J# | mm | 18.0 | # 14 |
| | #####15kN# | mm | 19.5 | # 14 |

#####.
#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com