



#####

SAFETYSTAR S3 LOW

SFTYSTRS3L

S3#####

SAFETY STAR S3 LOW#####S3#####SR
#####

##

#####

#####

SJ##

#####

PU

#####

S3 / SR, SC, #####,

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315

0.600 kg

ASTM F2413:2018

EN ISO 20345:2022+A1:2024



S3

##########
##########
#####



SRC###

##########1##
##SRC#####SRA#SRB#####

###



BLK



##########

##



##########WRU#

###



####

##########
#####100 KiloOhm##1 GigaOhm
#####



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
##, ##, ##, #####

#####:
#####, #####, #####

#####:
#####, #####, #####

#####	#####	##	EN ISO 20345
#####	#####	mg/cm ² /h	2.8
	#####	mg/cm ²	31
##	#####	mg/cm ² /h	64.8
	#####	mg/cm ²	518
#####	SJ##	#####	25600/12800
#####	PU	#####	25600/12800
	#####	mm ³	92
	##### - #####NaLS - #####	#####	# 150
	##### - #####NaLS - #####	#####	0.38
	SR ### - ##### - #####	#####	# 0.31
	SR##### - ##### - #####	#####	0.36
	SR##### - ##### - #####	#####	# 0.36
	SR##### - ##### - #####	#####	0.36
	SR##### - ##### - #####	#####	# 0.19
	SR##### - ##### - #####	#####	0.34
	SR##### - ##### - #####	#####	# 0.22
	SR##### - ##### - #####	#####	72.2
	ESD#	#####	0.1 - 100
	SR##### - ##### - #####	N/A	0.1 - 100
	SR##### - ##### - #####	J	30
#####	###	mm	N/A
	#####100J#	mm	N/A
	#####10kN#####	mm	15.0
	#####200J#	mm	# 14
	#####15kN#	mm	19.0
#####	#####		# 14

#####:

#####Safety Jogger#####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com