

Medium

SAFETYSTAR S3 LOW

SFTYSTRS3L

S3

S3 ### #####. ### ## #, SR ### ## ##,
#####. ##, ## # ## ## ## #####.

#####

##

SJ Eco

##

PU

Top ##

S3 / SR, SC, CI, FO

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.600 kg


ASTM F2413:2018

EN ISO 20345:2022+A1:2024



S3

S3 #####
#####. # ## ##
#####.



##.




###.



SRC

#####. SRC #####
SRA # SRB #####
#####.



#####. 100##### 1### ## ##
##



###(WRU)

#####.



BLK

##:
##, ##, ##

##:
##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.8	# 0.8
	##: ### ##	mg/cm²	31	# 15
## ##	##			
	##: ### ##	mg/cm²/h	64.8	# 2
	##: ### ##	mg/cm²	518	# 20
##	SJ Eco			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
## #	PU			
	### ####(## ##)	mm³	92	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.38	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.36	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.36	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.34	# 0.22
	### ## #	###	72.2	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	30	# 20
	##			
Top	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	15.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	19.0	# 14

##:

###, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com