

Light

SPEEDY S3S

Fashionable mid-cut safety shoe for active professional

Safety Jogger SPEEDY is a mid-cut safety shoe with SR slip resistant soles, heat-resistant outsole, and metal-free composite toecap. Perfect for various industries and environments, it provides superior support, freshness, dryness, and protection.

Upper	Nubuck Action Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/Rubber (NBR)
Toecap	Composite
Category	S3S / SR, HI, CI, FO, HRO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.683 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



094



SJ Flex

Metal-free puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Composite toecap

Metal-free and lightweight, no thermal or electrical conductivity



Industries:

Automotive, Cleaning, Construction, Logistics, Industry

Environments:

Dry environment, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	3.9	# 0.8
	Upper: water vapor coefficient	mg/cm²	38.4	# 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	69.43	# 2
	Lining: water vapor coefficient	mg/cm²	555	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	93	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.55	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.44	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.34	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.23	# 0.22
	Antistatic value	MegaOhm	280.1	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com