



Light

SUN OB SLP

SUNOBSLP

Extremely comfortable, slip-resistant and ESD-compliant work sandal

The perfect companion to brighten up your workday. SUN OB has an open design that is extra breathable and comfortable, making both sweaty and sore feet a thing of the past. This slip-on shoe offers ESD protection and has a slip-resistant outsole that prevents slips, trips and falls. Made with lightweight and vegan materials.

| | |
|---------------|---|
| Upper | Synthetic Leather |
| Lining | N/A |
| Footbed | SJ foam footbed |
| Outsole | PU |
| Category | OB / SRC |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.199 kg |
| Norms | ASTM F3445:2021 EN ISO 20347:2012 |



BLK



WHT



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Vegan
Uses or contains no animal products.

Industries:

Cleaning, Medical, Food & beverages, Assembly

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.92 | # 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 18 | # 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | # 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | # 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 140 | # 150 |
| | Outsole slip resistance SRA: heel | friction | 0.42 | # 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.39 | # 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.16 | # 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | # 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 32 | # 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com