



#####

SUN OB SLP

SUNOBSLP

#####

SUN OB #####
ESD #####
#####

####	####
##	N/A
#####	SJ#####
#####	PU
#####	OB / SRC
#####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
#####	0.199 kg
##	ASTM F3445:2021 EN ISO 20347:2012



BLK



WHT



#####



SRC####
#####1##
##SRC#####SRA#SRB#####

####



####



#####



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
#####, ####, ####, ##

#####:
####

#####:
#####

####		####	##	EN ISO 20347
####	####			
	#####	mg/cm ² /h	1.92	# 0.8
	#####	mg/cm ²	18	# 15
##	N/A			
	#####	mg/cm ² /h	N/A	# 2
	#####	mg/cm ²	N/A	# 20
####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	PU			
	#####	mm ³	140	# 150
	##### SRA#####	#####	0.42	# 0.28
	##### SRA#####	#####	0.39	# 0.32
	##### SRB#####	#####	0.16	# 0.13
	##### SRB#####	#####	0.19	# 0.18
	#####	#####	N/A	0.1 - 1000
	ESD#	#####	N/A	0.1 - 100
	#####	J	32	# 20

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com