



#####

TANA P1

TANAP1

#####

###TANA P1#####
#####ESD#####TANA P1###
#####

SJ#####
N/A
####/##

P1 / SR, ESD, #####, HRO
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.400 kg
EN ISO 20346:2022



3D####

#####

#####



#####WRU#

#####

#####



(SR)

#####SRA+SRB=SRC#####

#####



#####

#####

#####



#####

#####

#####



BLK

#####:
#####, #####, #####, #####, #####

#####:
#####, #####, #####

#####:
#####

####		####	#	EN ISO 20346
####	####			
	#####	mg/cm ² /h	1.2	# 0.8
	#####	mg/cm ²	18.5	# 15
##	####			
	#####	mg/cm ² /h	58.06	# 2
	#####	mg/cm ²	424	# 20
#####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/####			
	#####	mm ³	128g/ cm ³ (Density:1.17mm ³)	# 150
	##### - #####NaLS - #####	####	0.43	# 0.31
	##### - #####NaLS - #####	####	0.44	# 0.36
	SR ##### - ##### - #####	####	0.37	# 0.19
	SR##### - ##### - #####	####	0.35	# 0.22
	#####	####	72.5	0.1 - 1000
	ESD#	####	31	0.1 - 100
	#####	J	30	# 20
#####	#####			
	#####100J#	mm	21.0	# 13
	#####10kN#####	mm	21.5	# 13
	#####200J#	mm	N/A	N/A
	#####15kN#	mm	N/A	N/A

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com