

# SAFETY JOGGER

## INDUSTRIAL

FOOD


### W310 S2

Low-cut safety shoe, designed for the food industry

Upper	Synthetic Leather
Outsole	PU/PU
Toecap	Composite
Midsole	N/A
Lining	3D-Mesh
Footbed	Max 3Fit
Safety category	EN ISO 20345 - S2 / SRC
Sample weight	0.470 gr.
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 / CM 23.0-31.5



WHT



#### METAL FREE

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



#### VEGAN

Uses or contains no animal products.



#### VEGAN LORICA®

Lorica® is a high-tech synthetic with excellent softness and durability. Protects effectively against animal fats, oils, petrol, disinfectants and a variety of chemicals.



#### HACCP

HACCP is a testing system based on a risk analysis. Identifies, evaluates and eliminates significant health risks, associated with foods, that can lead to disease of consumers, be identified, assessed and eliminated. The specially for the food industry developed and HACCP

# SAFETY JOGGER

## INDUSTRIAL

FOOD

## W310 S2

### Industries:

Automotive, Catering, Chemical, Cleaning, Food & beverages, Medical

### Environments:

Dry environment, Wet environment

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	0.88	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	16.5	≥ 15
<b>Lining</b>	<b>3D-Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	2.2	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	22	≥ 20
<b>Footbed</b>	<b>Max 3Fit</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	198	≤ 150
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	612	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	22	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
41