



Medium


W310 S2

Low-cut safety shoe, designed for the food industry

Upper	Synthetic Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	N/A
Outsole	PU/PU
Toecap	Composite
Category	S2 / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.520 kg
Norms	EN ISO 20345:2011



WHT



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Vegan
Uses or contains no animal products.



Vegan Lorica®
Lorica® is a high-tech synthetic with excellent softness and durability. Protects effectively against animal fats, oils, petrol, disinfectants and a variety of chemicals.



HACCP
HACCP is a testing system based on analysis (identification, evaluation and elimination) of significant health risks, associated with foods, that can lead to disease of consumers. The specially for the food industry developed and HACCP equitable models are made from washable materials.

Industries:

Automotive, Catering, Chemical, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Synthetic Leather			
	Upper: permeability to water vapor	mg/cm ² /h	0.88	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	16.5	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	2.2	≥ 2
	Lining: water vapor coefficient	mg/cm ²	22	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	198	≤ 150
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	612	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	22	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.