



#####

X1100N79 SB

 ##X1100N79##SR#####
 #####SJ#####

####	#####
##	##
####	##
#####	#####
#####	PU/PU
#####	#####
####	SB / ##, SR, WPA, E, #####, #####
####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
#####	0.710 kg
##	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



#####EH#
 EH#Electrical hazard#####
 #####



 #####



 #####
 #####



SRC###
 #####1##
 ##SRC#####SRA#SRB#####
 #####
 ####



SJ####
 #####
 #####
 100#####



 #####

####:
 ####, ##, #####, ##, #####, ####, #####

#####:
 ####, #####, ####, ##, #####, #####

#####:
 #####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm ² /h	2.86	# 0.8
	#####	mg/cm ²	30	# 15
##	###			
	#####	mg/cm ² /h	40.21	# 2
	#####	mg/cm ²	323	# 20
#####	###			
	#####	####	25600/12800	25600/12800
#####	PU/PU			
	#####	mm ³	33	# 150
	##### - #####NaLS - #####	#####	0.39	# 0.31
	##### - #####NaLS - #####	#####	0.36	# 0.36
	SR ### - ##### - #####	#####	0.30	# 0.19
	SR##### - ##### - #####	#####	0.26	# 0.22
	#####	#####	N/A	0.1 - 1000
	ESD#	#####	N/A	0.1 - 100
	#####	J	31	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	16.5	# 14
	#####15kN#	mm	21.5	# 14

#####.

#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION

Proudly ranked in the top 1% by EcoVadis for sustainability.

