



SAFETY JOGGER

INDUSTRIAL

X1100N79 SB

X110ON79 ##### SR #####
SJ Flex

#####	#####
#####	#####
#####	#####
#####	#####
#####	PU/PU
#####	#####
#####	SB / #.#, ###.###, ##, ##, ##.##, #####
#####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
#####	JPN 21.5-31.5 / KOR 230-315
#####	0.710 kg
#####	ASTM F2413:2018
#####	EN ISO 20345:2022+A1:2024



BLK



#####

SRC

```
#####
#####SRC #####SRA ## SRB#####
#####
```

#####

**SAFETY
JOGGER
WORKS**

HEAD-TO-TOE PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED
IN EUROPE
www.safetyjogger.com

#####:

#####:

#####:####:

#####

#####	#####	#####	#####	EN ISO 20345
#####	#####	##./##./##	2.86	# 0.8
#####	#####	##./##	30	# 15
#####	#####	##./##./##	40.21	# 2
#####	#####	##./##	323	# 20
#####	#####	##	25600/12800	25600/12800
PU/PU				
#####	##### (#####)	##	33	# 150
##### - ##### + NaLS - #####	#####	##	0.39	# 0.31
##### - ##### + NaLS - #####	#####	##	0.36	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	##	0.30	# 0.19
##### SR - ##### + ##### - #####	#####	##	0.26	# 0.22
#####	#####	N/A	0.1 - 1000	
### ESD	#####	N/A	0.1 - 100	
#####	##	31	# 20	
#####	#####			
##### (##### 100J)	##	N/A	N/A	
##### (##### 10kN)	##	N/A	N/A	
##### (##### 200J)	##	16.5	# 14	
##### (##### 15kN)	##	21.5	# 14	

#####:

Safety Jogger