



###

XPLORE S3S

#####

Safety Jogger XPLORE#####SR#####
##########
#####

SJ#####

PU/##

S3S / SR, #####, HRO
EU 38-47 / UK 5.0-12.0 / US 5.5-13.0
JPN 24-31 / KOR 250-310
0.770 kg
ASTM F2413:2018
EN ISO 20345:2022



HRO#
#####300#####



#####




SRC#####
#####1#
##SRC##SRA##SRB##

###



#####



SJ#####

100#####



032

#####:
#####, ##, ####, #####, ####

#####:
####, #####, ####

#####:
#####

####	####	##	EN ISO 20345
####	#####		
	#####	mg/cm ² /h	8.1
	#####	mg/cm ²	69.7
##	####		
	#####	mg/cm ² /h	67.6
	#####	mg/cm ²	541
####	SJ#####		
	#####	####	25600/12800
#####	PU/##		25600/12800
	#####	mm ³	98.8
	##### - #####NaLS - #####	#####	0.51
	##### - #####NaLS - #####	#####	0.47
	SR ### - ##### - #####	#####	0.23
	SR##### - ##### - #####	#####	0.22
	####	#####	24.3
	ESD#	#####	N/A
	#####	J	46
#####	####		
	#####100J#	mm	N/A
	#####10kN#####	mm	N/A
	#####200J#	mm	17.0
	#####15kN#	mm	20.0

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com